

DECLARATION OF PERFORMANCE
In accordance with annex III of Regulation (EU) 305/2011

No. BAL049-CPR/2013


1. Unique identification code of the product-type:
BAL Micromax Sealant
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):
See batch number and date of manufacture on packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Non-structural sealant for sanitary joints. EN 15651-3:XS1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):
**Building Adhesives Limited,
Newstead Industrial Estate,
Longton Road,
Trentham,
Stoke on Trent,
Staffordshire,
ST4 8JB**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
EN 15651-3:2012
Laboratory 0370 conducted Initial Type Testing under System 3.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class F	
Release of Chemicals	See SDS	
Water Tightness and Air Tightness as determined by: Resistance to flow Loss of volume Tensile properties at maintained extension Adhesion/cohesion properties at variable temperatures Adhesion/Cohesion at maintained extension after immersion in water Microbial growth Durability	$\leq 3\text{mm}$ $\leq 10\%$ No failure No failure No failure 0 Pass	EN 15651-3:2012 Conditioning method B. Tested on glass substrate, no primer

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: David Longwell – Technical Manager



Stoke on Trent 05.08.14