



## SAFETY DATA SHEET BAL RAPIDSET GREY

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name BAL RAPIDSET GREY

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cement based adhesive.  
Uses advised against No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

Supplier Building Adhesives Ltd  
Longton Road,  
Trentham,  
Stoke on Trent  
ST4 8JB  
01782 591100  
Contact Person sdsreply@building-adhesives.com

#### 1.4. Emergency telephone number

01782 591100 (7am-8pm)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Skin Irrit. 2 - H315; Eye Dam. 1 - H318; Skin Sens. 1 - H317; STOT SE 3 - H335
Environment	Not classified.

Classification (1999/45/EEC) Xi; R37/38, R41. R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

When the cement based powder is mixed with water or admixture, a strongly alkaline paste is produced. Cement based products may, until set, cause both irritant and allergic contact dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts. Corrosive. Prolonged contact causes serious eye and tissue damage.

Environment

The product is not expected to be hazardous to the environment.

#### 2.2. Label elements

Contains CALCIUM SULFOALUMINATE CEMENT  
ORDINARY PORTLAND CEMENT

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

## BAL RAPIDSET GREY

	H318	Causes serious eye damage.
	H335	May cause respiratory irritation.
Precautionary Statements		
	P102	Keep out of reach of children.
	P261	Avoid breathing dust.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements		
	P271	Use only outdoors or in a well-ventilated area.
	P272	Contaminated work clothing should not be allowed out of the workplace.
	P261	Avoid breathing vapour/spray.
	P264	Wash contaminated skin thoroughly after handling.
	P321	Specific treatment (see medical advice on this label).
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P310	Immediately call a POISON CENTER or doctor/physician.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P362	Take off contaminated clothing and wash before reuse.
	P363	Wash contaminated clothing before reuse.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
	P405	Store locked up.
	P501	Dispose of contents/container to ...

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

CALCIUM SULFOALUMINATE CEMENT	5-10%
CAS-No.: 12004-14-7	EC No.:
Classification (EC 1272/2008) Eye Dam. 1 - H318, H319 Eye Irrit. 2 - H318, H319 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R36/37,R41. R43.
ORDINARY PORTLAND CEMENT	10-30%
CAS-No.: 65997-15-1	EC No.: 266-043-4
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC) Xi;R37/38,R41. R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### Composition Comments

This product contains a reducing agent to ensure that the CrVI content of the cement in the product remains below 2ppm during the defined shelf life of the product.

## SECTION 4: FIRST AID MEASURES

# BAL RAPIDSET GREY

## **4.1. Description of first aid measures**

General information

Consult a physician for specific advice.

Inhalation

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention immediately!

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water.

Get medical attention if irritation persists after washing.

Eye contact

Remove victim immediately from source of exposure. Do not rub eye. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

## **4.2. Most important symptoms and effects, both acute and delayed**

Inhalation

Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Ingestion

May cause chemical burns in mouth and throat.

Skin contact

May cause serious chemical burns to the skin.

Eye contact

May cause severe irritation to eyes. May cause blurred vision and serious eye damage.

## **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Extinguishing media

The product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### **5.2. Special hazards arising from the substance or mixture**

Hazardous combustion products

During fire, toxic gases (CO, CO<sub>2</sub>) are formed.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

Specific hazards

In case of fire, toxic gases may be formed.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

No specific fire fighting procedure given.

Protective equipment for fire-fighters

Wear full protective clothing.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet.

### **6.2. Environmental precautions**

Do not discharge into drains, water courses or onto the ground.

### **6.3. Methods and material for containment and cleaning up**

Avoid contact with skin or inhalation of spillage, dust or vapour. Dampen spillage with water. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer. Shovel into dry containers. Cover and move the containers. Flush the area with water.

# BAL RAPIDSET GREY

## 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Provide good ventilation. Avoid handling which leads to dust formation.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
CALCIUM SULFOALUMINATE CEMENT	WEL		4 mg/m <sup>3</sup> resp.dust			
ORDINARY PORTLAND CEMENT	WEL		4 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Dust mask/respirator.

Hand protection

Use suitable protective gloves if risk of skin contact.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Powder, dust
Solubility	Slightly soluble in water.
pH-Value, Conc. Solution	12-13

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### **10.1. Reactivity**

No specific reactivity hazards associated with this product.

### **10.2. Chemical stability**

Stable under normal temperature conditions.

### **10.3. Possibility of hazardous reactions**

Not applicable.

### **10.4. Conditions to avoid**

Avoid contact with acids. Water, moisture.

### **10.5. Incompatible materials**

Materials To Avoid

Strong acids. Aluminium powder

### **10.6. Hazardous decomposition products**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1. Information on toxicological effects**

Inhalation

May cause irritation to the respiratory system. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Ingestion

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin contact

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

Eye contact

Risk of serious damage to eyes. May cause chemical eye burns.

Health Warnings

Repeated exposure in excess of the WEL has been linked with rhinitis and coughing. Skin exposure has been linked to allergic chromium dermatitis.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

### **12.1. Toxicity**

The product is not expected to be hazardous to the environment (LC<sub>50</sub> aquatic toxicity rating not determined). The addition of cement based product to water will, however, cause the pH to rise and may, therefore, be toxic to aquatic life in some circumstances.

### **12.2. Persistence and degradability**

Not relevant. After hardening, cement presents no toxicity risks.

Degradability

There are no data on the degradability of this product.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential

No data available on bioaccumulation.

### **12.4. Mobility in soil**

## BAL RAPIDSET GREY

Mobility:

The product is non-volatile. The product is insoluble in water and will sediment in water systems.

### **12.5. Results of PBT and vPvB assessment**

No information available.

### **12.6. Other adverse effects**

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Product that contains >2ppm CrVI should be disposed of according to local legislation or should be treated with a reducing agent before use. Product that is within shelf life may be hydrated with water and disposed of according to local legislation. The hydrated product is not hazardous.

## SECTION 14: TRANSPORT INFORMATION

General	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
Road Transport Notes	Not Classified
Rail Transport Notes	Not classified.
Sea Transport Notes	Not classified.
Air Transport Notes	Not classified.

### **14.1. UN number**

Not applicable.

### **14.2. UN proper shipping name**

Not applicable.

### **14.3. Transport hazard class(es)**

Not applicable.

Transport Labels

No transport warning sign required.

### **14.4. Packing group**

Not applicable.

### **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant

No.

### **14.6. Special precautions for user**

Not applicable.

### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

## SECTION 15: REGULATORY INFORMATION

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

# BAL RAPIDSET GREY

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

## 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

### SECTION 16: OTHER INFORMATION

#### Revision Comments

1

Issued By Technical Manager

Date 21.05.15

#### Risk Phrases In Full

R36/37 Irritating to eyes and respiratory system.

R37/38 Irritating to respiratory system and skin.

R43 May cause sensitisation by skin contact.

R41 Risk of serious damage to eyes.

#### Hazard Statements In Full

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.