BAL

wall tiling

Wall Tile Adhesive Selector

	READY MIXED				STANDARD SETTING		RAPID SETTING	STANDARD SETTING FLEX		RAPID SETTING FLEX			EPOXY-RESIN
	Green Star	Blue Star	White Star Plus	Tile & Grout	Gold Star	ctf4	Supercover Rapidset	Single Part Flexible	Max-Flex Fibre	Supercover Rapidflex	Rapidset Flexible	Rapidset Flexible Fibre	Easypoxy AG
LOCATION													
Interior (dry)	■	■	■	■	■	■	■	■	■	■	■	■	■
Exterior	–	–	–	–	■	■	■	■	■	■	■	■	■
ENVIRONMENTS													
Intermittent wet*	E	E	■	■	■	■	■	■	■	■	■	■	■
Power shower	–	–	■	■	■	■	■	■	■	■	■	■	■
Communal shower	–	–	■	–	■	■	■	■	■	■	■	■	■
Swimming pool	–	–	–	–	■	■	▲	■	■	■	■	■	■
Minor vibration	–	–	■	■	▲	▲	▲	■	■	■	■	■	■
Limited movement	–	–	■	–	–	–	–	–	■	–	–	–	■
BACKGROUNDS													
Lightweight block	–	–	–	–	▲ & ✱	▲ & ✱	▲ & ✱	✱	✱	✱	✱	✱	■
Render, Standard brick/block	■	■	■	■	■	■	■	■	■	■	■	■	■
Concrete, Dense brick/block	–	–	–	–	▲	▲	▲	■	■	■	■	■	■
Plaster	■	■	■	■	■	■	✱	✱	✱	✱	✱	✱	■
Plasterboard	■	■	■	■	■	■	■	■	■	■	■	■	■
Tilebacker boards, Fibre reinforced cement boards	D	D	D	D	▲	▲	▲	■	■	■	■	■	■
Existing Tiles: glazed ceramics	D	D	D	D	▲	▲	▲	–	■	–	–	1:3	■
Existing Tiles: unglazed ceramics, Natural stone	■	■	■	■	▲	▲	■	■	■	■	■	■	■
Plywood walls	–	–	■	■	▲	▲	▲	–	■	–	–	1:3	■
Lightweight Tilebacker boards	D	D	D	D	▲	▲	▲	■	■	■	■	■	■

Wall Tile Grout Selector

	CEMENTITIOUS		PRO-HYGIENE SYSTEMS		EPOXY-RESIN
	Bal Grout	Superflex	Microflex	Micromax2	Easypoxy AG
LOCATION					
Interior (dry)	■	■	■	■	■
Exterior	■	■	■	■	■
ENVIRONMENTS					
Intermittent wet*	■	■	■	■	■
Power shower	–	■	■	■	■
Communal shower	■	■	■	■	■
Swimming pool	1:2	■	■	–	■
Minor vibration	1:2	■	■	■	■
Limited movement	1:2	■	■	■	■
SPECIFIC FEATURES					
Antibacterial	–	–	■	■	–
Hygienic/sterile – food use	–	–	–	–	■
Chemical resistant	–	–	–	–	■

BAL 25 YEAR 25 YEAR GUARANTEE

KEY

- ■ = Suitable product
- ▲ = Use product with Admixture* (1:1)
- 1:2 = Use product with Admix AD1* (1:2)
- 1:3 = Use product with Admix AD1* (1:3)
- E = Use product with BAL Easypoxy AG
- ✱ = Use product with BAL Prime APD
- D = Longer drying time (min. 3 days)

*Kitchen/Bathroom/Domestic shower

**BAL Admix AD1 used with adhesives, BAL Admix GT1 used with grouts

For complete information on the background preparation and application of these products, refer to the Technical Data Sheets or call the BAL Technical Advisory Service on 0845 600 1222

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract, tort or otherwise) whatsoever for any loss, damage or expense arising from the misuse of any Information it supplies nor for the use of any Information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or to update Information from time to time.

www.bal-adhesives.com

BAL3260215