

wall tiling guidance

Wall Tile Adhesive Selector

READY MIXED										STANDARD SETTING	RAPID SETTING	STANDARD SETTING FLEX		RAPID SETTING FLEX			SPECIALIST	EPOXY-RESIN
Blue Star		Tile & Grout		Green Star	White Star Plus		ct4	Supercor Rapidset	Single Part Flexible	Max-Flex Fibre	Supercor Rapidflex	Rapidset Flexible	Rapidset Flexible Fibre	Single Part Fastflex	Easyoxy AG			
LOCATION																		
Interior (dry)																		
Exterior																		
ENVIRONMENTS																		
Intermittent wet*																		
Power shower																		
Communal shower																		
Swimming pool																		
Minor vibration																		
Limited movement																		
BACKGROUNDS																		
Lightweight block																		
Render, Standard brick/block																		
Concrete, Dense brick/block																		
Plaster																		
Plasterboard																		
Tilebacker boards, Fibre reinforced cement boards																		
Existing Tiles: glazed ceramics, Natural stone																		
Existing Tiles: unglazed ceramics																		
Plywood walls																		
Lightweight Tilebacker boards																		

Wall Tile Grout Selector

CEMENTITIOUS			ANTIMICROBIAL RANGE		EPOXY-RESIN
Bal Grout	Superflex	Microflex	Micromax2	Easyoxy AG	
LOCATION					
Interior (dry)					
Exterior					
ENVIRONMENTS					
Intermittent wet*					
Power shower					
Communal shower					
Swimming pool					
Minor vibration					
Limited movement					
SPECIFIC FEATURES					
Antibacterial					
Hygienic/sterile – food use					
Chemically resistant					



KEY	
■	= Suitable product
▲	= Use product with Admixure [†] (1:1)
◻	= Use product with Admixure [†] (1:2)
◻	= Use product with Admixure [†] (1:3)
◻	= Use product with BAL Easyoxy AG
◻	= Use product with BAL Prime APD
◻	= Longer drying time (min. 3 days)

* Kitchen/Bathroom/Domestic shower
[†] BAL Admix AD1 used with adhesives, BAL Admix G11 used with grouts

For complete information on the background preparation and application of these products, refer to the Technical Data Sheets or call the BAL Technical Advisory Service on 0845 600 1222

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract, tort or otherwise) whatsoever for any loss, damage or expense arising from the misuse of any information. It supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or to update information from time to time.



bal-adhesives.com



@BALtiling



BALtiling

