

floor tiling guidance

Floor Tile Adhesive Selector

STANDARD SETTING							RAPID SETTING		STANDARD SETTING FLEX		RAPID SETTING FLEX			POURABLE	SPECIALIST		EPOXY-RESIN		
ctf4							Supercover Rapidset		Max-Flex Fibre		Supercover Rapidflex		Rapidset Flexible Fibre			Stone & Tile PTB	Green Screed		Easyoxy AG
[STANDARD SETTING]							[RAPID SETTING]		[STANDARD SETTING FLEX]		[RAPID SETTING FLEX]			[POURABLE]	[SPECIALIST]		[EPOXY-RESIN]		
LOCATION																			
Interior (dry)									Interior (dry)										
Exterior									Exterior										
ENVIRONMENTS																			
Intermittent wet*									Intermittent wet*										
Power shower									Power shower										
Communal shower									Communal shower										
Swimming pool									Swimming pool										
Minor vibration/Heavy use									Minor vibration/Heavy use										
Limited deflection									Limited deflection										
BASES																			
Cement:sand screed/Concrete									Cement:sand screed/Concrete										
Flooring grade asphalt									Flooring grade asphalt										
Anhydrite screed									Anhydrite screed										
Underfloor heated screeds									Underfloor heated screeds										
Plywood overlay									Plywood overlay										
Tongue & groove floorboards									Tongue & groove floorboards										
Vinyl tiles/sheets									Vinyl tiles/sheets										
Concrete fibre boards									Concrete fibre boards										
Uncoupling membrane** (such as BAL Rapid-Mat)									Uncoupling membrane** (such as BAL Rapid-Mat)										
Existing tiles: glazed									Existing tiles: glazed										
Existing tiles: unglazed, Hard natural stone									Existing tiles: unglazed, Hard natural stone										
[STANDARD SETTING]							[RAPID SETTING]		[STANDARD SETTING FLEX]		[RAPID SETTING FLEX]			[POURABLE]	[SPECIALIST]		[EPOXY-RESIN]		

Floor Tile Grout Selector

CEMENTITIOUS			ANTIMICROBIAL	EPOXY-RESIN	
Wide Joint			Superflex Wide Joint	Micromax2	Easyoxy AG
[CEMENTITIOUS]			[ANTIMICROBIAL]	[EPOXY-RESIN]	
LOCATION					
Interior (dry)			Interior (dry)		
Exterior			Exterior		
ENVIRONMENTS					
Intermittent wet*			Intermittent wet*		
Domestic shower			Domestic shower		
Power shower			Power shower		
Communal shower			Communal shower		
Swimming pool			Swimming pool		
Minor vibration/Heavy use			Minor vibration/Heavy use		
Limited deflection			Limited deflection		
SPECIFIC FEATURES					
Antibacterial			Antibacterial		
Hygienic/sterile – food use			Hygienic/sterile – food use		
Chemically resistant			Chemically resistant		
Moderate trafficking			Moderate trafficking		
Heavy trafficking			Heavy trafficking		
[CEMENTITIOUS]			[ANTIMICROBIAL]	[EPOXY-RESIN]	



KEY

- = Suitable product
- ▲ = Use product with Admixure[†] (1:1)
- ☒ = Use product with Admixure[†] (1:2)
- ☒ = Use product with Admixure[†] (1:3)
- ◻ = Use product with BAL Bond SBR
- ☒ = Use product with BAL Prime APD
- ☒ = Use product with BAL Rapid-Mat

* Kitchen/Bathroom/Domestic shower
 ** Can vary with matting system used.
 For guidance, contact BAL Technical Advisory Service

[†] BAL Admix AD1 used with adhesives, BAL Admix G11 used with grouts

For complete information on the background preparation and application of these products, refer to the Technical Data Sheets or call the BAL Technical Advisory Service on 0845 600 1222

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract, tort or otherwise) whatsoever for any loss, damage or expense arising from the misuse of any information. It supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or to update information from time to time.



bal-adhesives.com

