

AquaDrain[®] TM

Height adjustable, ultra-flat drain grate for thin covering external tiling from 31mm.

DESCRIPTION

The AquaDrain[®] TM drain grate, with its extremely shallow frame, is suitable for thin-layer, tile and natural stone floor coverings using direct or point adhesion fixing method on the AquaDrain[®] T+ surface drainage matting. For full application advice, please refer to Part A Technical Design Guide or contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE.

Product Properties and Benefits

- Use in front of doors, floor level windows components or for in line drainage.
- Allows safe drainage of outdoor surfaces at door thresholds. Only 31 mm construction height.
- Simply cut to length.
- Can be used with AquaDrain[®] T+ and AquaDrain[®] EK drainage matting.
- Integral dirt trap protects against fouling, guaranteeing permanent drainage performance.
- Easy height adjustment thanks to six continuously adjustable screw feet.
- Maximum drainage performance combined with AquaDrain[®] T+ and AquaDrain[®] EK systems for external tiling.
- Ideal for use in wheelchair accessible applications.

PRODUCT INFORMATION

Composition: Steel galvanised or stainless steel.

Dimensions: Width 100mm x Length 1000mm, including 6 screw feet and 3 load distribution plates

Length: can be continuously adjusted from 1000 mm to 770mm, 560mm to 410mm, 190mm to 110mm.

Height adjustment:
Height adjustable 31-46 mm


Minimum installation height: 30mm is screw foot can be cut on site.

Note: For marine installations stainless steel grade 316 is recommended.


AquaDrain[®] Lochwinkel perforated screed angle
Composition – high dipped powder coated steel

Dimensions - 30/40mm x 1.000mm (powder coated steel).












AquaDrain[®] TM



AquaDrain[®] Lochwinkel



OPTIONAL SYSTEM COMPONENTS

<p>AquaDrain® T+ drainage mat</p> 	<p>DiProTec® AB-KV sealing tape</p> 	<p>AquaDrain® SK joint tape</p> 	<p>AquaDrain® Edge insulation tape</p> 
<p>AquaDrain® TM drain grate</p> 	<p>ProRin® BR guttering</p> 	<p>ProFin® DP edge profile and BL facing plate</p> 	<p>ProFin® V22/55 drip/drain edge profile</p> 
<p>BAL Stone and Tile PTB</p> 	<p>MorTec® SOFT silicone sealant</p> 	<p>BAL Tank-it</p> 	

N.B Please consult BAL Technical Advisory and Specification Service (TAS) or a member of the BAL specification support team for a full and comprehensive product specification to meet your project requirements

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

SHELF LIFE

No shelf life when stored under normal conditions. Protect from frost, damp and sunlight.

6 YEAR GUARANTEE

Since 1990, GUTJAHR has been the only manufacturer to offer extended warranties for its drainage systems, e.g. 6 years for balconies, patios and outdoor steps with AquaDrain® drainage.

No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control. *Contact BAL Marketing Department for full details.*

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale. *Available on request. For sales and technical queries, contact:*

BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB,
England www.bal-adhesives.com

Sales Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical Tel: +44 (0) 1782 591120 or +44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

Unit 622, Phase III

Northwest Business Park

Ballycoolin, Dublin 15, Ireland

Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.