





Profin V22/55

Drainage profiles, corner units and connectors for AquaDrain surface drainage systems.


DESCRIPTION

Aluminium powder-coated drip/drain end profile and corner unit for use with Gutjahr external tiling systems from BAL. Available in heights of 22 mm and 55 mm, these edge profiles cover the AquaDrain assembly to create a clean, neat and functional finish to the balcony surround. The projecting profile directs surface water away and keeps drainage channels free. For full installation advice and technical drawings please refer to Part A Technical Design Guide or contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE.

Product Properties and Benefits

- Surface and seepage water is drained away without leaving dirt trails on balconies and facades and without danger of blocking.
- Decorative edging and screed support in one. Raised edge profile provides a facing for unglazed edge of tiles.
- Protects screed from water damage.
- Rapid and simple installation. Profiles can be linked with profile connectors supplied.
- Prefabricated with seal-tight welded corners for easy assembly.
- Use ProFin[®] V22 in combination with direct point adhesion fixing method on AquaDrain[®] T+ surface drainage mats for covering thickness from 22 mm.
- Use ProFin[®] V55 in combination with AquaDrain[®] EK drainage roll or sheets.
- Ideal to be used for Roof Terraces with existing membrances already present on-site.
- For upstand heights of 22 mm or 55 mm.

ProFin® V22



PRODUCT INFORMATION


Composition: ProFin® V22/55 profiles and Corner 90° unites are constructed from power coated aluminium.

Colour: Alumetallic. Other colours available on request. **Size:** 1 length = 3 m 1 corner unit = 185 mm x 185 mm

Additional Information:

 Height of structure depends on the type of construction and covering. (See chart on page 2)

ProFin® V55




ProFin® V55

Corner 90°

185 mm

90°



OPTIONAL SYSTEM COMPONENTS

A 5 . 9 51/ T	D:D T @ 4D 104 1: 1		
AquaDrain® EK or T+	DiProTec® AB-KV sealing tape	AquaDrain® SK joint tape	AquaDrain® Edge insulation tape
drainage mat			
AquaDrain® TM or FLEX	AquaDrain® Lochwinkel screed	ProRin®BR guttering	ProFin® DP edge profile and BL
drain grate	angle		facing plate
B			c na
ProFin® V22/55 drip/drain	BAL Tank-it	MorTec® DRAIN	BAL Quickset Cement
edge profile			
	TRAL Carlois		quickset cement
BAL Rapidset Flexible Fibre	BAL Stone and Tile PTB	BAL Micromax2 Grout	BAL Micromax Sealant
rapidset flexible fibre the state of the st	stone & tile ptb ptb which address in the state of the	RICTORIAL EL MACEDIO DE LA MACEDIO DELA MACEDIO DE LA MACEDIO DE LA MACEDIO DE LA MACEDIO DE LA MACE	
MorTec® SOFT silicone			
sealant			

N.B Please consult BAL Technical Advisory and Specification Service (TAS) or a member of the BAL specification support team for a full and comprehensive product specification to meet your project requirements.

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

SHELF LIFE

No shelf life when stored under normal conditions Protect from frost, damp and sunlight.

6 YEAR GUARANTEE

Since 1990, GUTJAHR has been the only manufacturer to offer extended warranties for its drainage systems, e.g. 6 years for balconies, patios and outdoor steps with AquaDrain® drainage.

No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control. *Contact BAL Marketing Department for full details*.

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale. *Available* on request. For sales and technical queries, contact:

BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, Englandwww.bal-adhesives.com Sales Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical Tel:+44 (0) 1782 591120 or+44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

Unit 622, Phase III Northwest Business Park Ballycoolin, Dublin 15, Ireland Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.