

board

Non-hazardous water-resistant and easy to cut tile backerboard for walls & floors

DESCRIPTION

Strong, durable, fire rated non-hazardous, water/mould and impact-resistant tile backer board for wall & floors.

Use for

- Providing a complete and easy to use BAL tiling solution.
- Easy to cut and easy to use water and mould-resistant tile backer board. Provides a stable substrate to both wall and floor.
- Suitable for dry or wet interior environments prior to fixing wall and floor tiles.
- Use to paint or wallpaper over when rooms are not to be fully tiled.

The board provides a stable substrate for most types of tile/stone and will take a maximum weight of 100kg per m² when fixed to a solid background. Is ideal in association with an approved design for:

- Heavy Duty Showers and Power Showers*
- Wet Rooms*
- Kitchens, bathrooms, laundry and utility rooms
- Fireplaces and open burners*
- Boxing around pipes and bath panels
- Underfloor heating
- Swimming Pool areas*
- Use with more than one type of finish i.e. painted and tiled areas
- Fixing accessories such as toilet roll holders, shower curtain rails, mirrors, shelves etc. (Note: heavy fixings must be screwed to the supporting wall/noggins)

**Further technical guidance may be required prior to the use in wet installations to ensure they are incorporated as part of an approved construction. Please contact the BAL TECHNICAL ADVISORY SERVICE for free advice.*

Restrictions: NOT suitable for

- Exterior use
- Swimming Pool Tank

PRODUCT INFORMATION

Composition: Magnesium oxide board, inorganic substances and alkaline resistant fibreglass mesh. Low energy manufacturing process.

Colours: White

Type: Internal use only

Sizes: 1200mm x 600mm

Thickness: Floors - 6mm and 12mm

Walls – 12mm only

Key Features:

- Simple, easy to handle, fix and with dust free cutting.
- Water-resistant.
- Hold a maximum weight limit 100kg per m².*
- Provides a strong and stable surface for finishes.
- Ideal for fixing most finishes including:
 - Tiles/ stone and mosaics.
 - Emulsion and oil based paints and wallpaper.
 - Plaster and render applications.
- Tested and approved to BBA
- Ideal for power showers, wet rooms.

Tile after: Once securely fixed and rigid, tiling can be started immediately.

USAGE & SERVICE CONDITIONS

Walls	✓	Floor	✓
Interior	✓	Exterior	✗
Dry	✓	Wet (1)(2)	✓
Swimming Pool areas (1)(3)	✓	Showers (2)(a)	✓
Internal Domestic and Commercial	✓	Steam Rooms (1)(2)(3)	✓
Worktops/ Countertops (3)	✓	Underfloor Heating	✓
Bath Panels & Tub Decks	✓		

BACKGROUNDS / BASES

Flush Transitions to Drywall	✓
Over Timber Subfloors	✓
Over Concrete Subfloors	✓
Over Timber Floors	✓

- (1) Tiles may be grouted using BAL EASYPOXY AG.
 (2) In wet conditions tank out with BAL TANK-IT or BAL WATERPROOFING KIT FOR SHOWERS.
 (3) Further technical guidance may be required. Contact BAL Technical Advisory Service for further information.

Note:

- (a) Do not use shower for at least 2 weeks after completion of grouting – BS 5385:Part 4.

SURFACE PREPARATION

GENERAL

Ensure surfaces to be tiled are flat, clean, sound and free from contamination.

1. Ensure any studwork is made from seasoned timber or suitable proprietary framework at maximum 300mm centres vertically and horizontally
2. When screw fixing BAL BOARD use stainless steel/ galvanized screws and ensure no fixings protrude. For walls apply fixings at a minimum of 15mm from the edge and 20mm from the corner of the board. When fixing, start at the centre and work outwards to prevent distortion within the boards. When fixing to walls, a 6mm gap should be left above the finished floor level to allow for settling of the frame or movement. All fixings should be flush with the surface of the board.
3. When tiling using BAL cementitious based tile adhesives, prime the face (rough face) of BAL BOARD with one coat of BAL PRIME APD (Diluted 1:1 by volume with water). Allow to dry before taping the board joints. No priming required for BAL WHITE STAR PLUS.
4. When using BAL BOARD for heavy weight coverings, additional fixings/anchors should be used.
5. All board joints must be reinforced using BAL SCRIM TAPE before tiling.
6. Tiling can commence once all preparation has been completed.

Wet Areas

In wet areas waterproof the background with BAL TANK-IT, or BAL WATERPROOFING KIT FOR SHOWERS.

Fill any voids or gaps over 1mm with suitable filler/adhesive or sealant, and allow curing.

Falls & Drainage

The floor substrate must be laid to the correct falls as recommended in BS 5385: Part 4. Gradients between 1:80 and 1:35 are recommended Falls of 1:80 should be the minimum; gradients steeper than 1:35 might be inconvenient and even dangerous. The drainage rate of the gulley/drain must exceed the flow rate of the water source i.e. shower head.

Surface regularity:

Surface Regularity is defined as the deviation in height of the surface of a flooring layer over short distances in a local area. In simpler terms, it is the 'flatness' or 'measure of unevenness' of the surface.

Class	MAXIMUM PERMISSABLE DEVIATION FROM a 2M STRAIGHT EDGE (MM)	APPLICATION
SR1	3mm	Recommended for direct fixing of tiles and slabs with a tile adhesive

SUITABLE SURFACES include:

Tongue and grooved floorboards/Existing timber sub floors

Ensure existing timber floors are flat (SR1) and (i) sufficiently rigid and stable (ii) can carry the additional static and dynamic load without excessive deflection; and (iii) have adequate ventilation under the timber. The timber floor should be dry, rigid and securely fixed (screwed to joints at 300mm centres, including any cross-noggings, if necessary). Sand (abrade) surface and ensure any surface coatings removed, e.g. varnish, lacquers etc, before priming with 2 coats of:

– BAL PRIME APD (undiluted) or

– BAL BOND SBR (diluted 1:2 by volume with clean water)

Allow each coat of primer to dry. Second coat applied at 90° to the first.

Fixing Method: Using a minimum 6mm notched trowel, apply a thin bed of BAL flexible tile adhesive to the floor such, see BAL TECHNICAL DATA SHEETS for further information on mixing and application. NOTE: Install the BAL BOARD in a broken bond or brick pattern and screw fix boards at 300mm centres into the existing floor. Before tiling, apply one coat of BAL PRIME APD (Diluted 1:1 by volume with water) to the rough face of the BAL BOARD and allow to dry. BAL SINGLE PART FASTFLEX can be selected or BAL RAPIDSET FLEXIBLE FIBRE combined with BAL RAPID MAT uncoupling membrane can be used when fixing ceramics or stone to BAL BOARD 6mm. Alternatively, providing the floor is stable and free from deflection, BAL RAPIDSET FLEXIBLE FIBRE can be used when fixing tiles to an overlay of 12mm thick BAL BOARD. For further advice, contact BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE.

Brickwork/Lightweight blockwork walling

Allow new block mortar to dry for minimum 6 weeks. There should be no evidence of damp present.

Fixing Method:

Screw fix the BAL BOARD into blockwork or brickwork at a maximum of 300mm centres horizontally and vertically using stainless steel galvanized screws. NOTE: install the 12mm BAL BOARD (broken bond or brick pattern). For uneven blockwork walls tile adhesive may be applied in addition to mechanical fixings. Before tiling apply one coat of BAL PRIME APD (Diluted 1:1 by volume with water) to the rough face of the BAL BOARD and allow drying. BAL RAPIDSET FLEXIBLE FIBRE can be used when fixing tiles on to BAL BOARD 12mm.

Dense concrete/blockwork walling

Allow new block mortar to dry for minimum 6 weeks. There should be no evidence of damp present.

Fixing Method (i): Screw fix the BAL BOARD at 300mm centres horizontally and vertically into the dense concrete blockwork using stainless steel galvanized screws. NOTE: Install the 12mm BAL BOARD in a broken bond or brick pattern. For uneven blockwork walls tile adhesive may be applied in addition to mechanical fixings. Before tiling apply one coat of BAL PRIME APD (Diluted 1:1 by volume with water) to the rough face of the BAL BOARD and allow to dry. BAL RAPIDSET FLEXIBLE FIBRE can be used when fixing tiles on to BAL BOARD 12mm.

Undertile electrical heating systems

NOTE: For further information on other backgrounds and preparation, contact BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE.

Flush Transitions to Drywall

Ensure the framing is structurally sound and complies with local building regulations. Using 12mm BAL BOARD, align the board with the connecting drywall area. All joints must align with studding.

Fixing Method:

Applying the boards horizontally, screw fix the 12mm BAL BOARDS at 300mm centres horizontally and vertically using stainless steel galvanized screws. NOTE: Install in a broken bond or brick pattern.

Over Concrete/Cement:Sand Screeds Subfloors

Before using BAL BOARD, ensure that the substrate is flat (SR1), free from efflorescence, laitance, dirt and other loose materials. Remove all barriers to adhesion including polished concrete by the use of suitable mechanical methods.

Allow the following minimum drying times:

- Concrete/concrete block walls/clay brickwork: 6 weeks
- Cement:sand screed: 3 weeks

Fixing Method:

Before installing prime all faces of the BAL BOARDS with BAL PRIME APD (Diluted 1:1 by volume with water) and allow to dry. Using a minimum 6mm notched trowel, apply a thin bed of BAL RAPIDSET FLEXIBLE FIBRE see BAL TECHNICAL DATA SHEET for further information on mixing and application. NOTE: install the 6mm or 12mm BAL BOARD in a broken bond or brick pattern. Tape the joints using BAL SCRIM TAPE. BAL RAPIDSET FLEXIBLE FIBRE or BAL STONE & TILE PTB can be used when fixing ceramics or stone to BAL BOARD 6mm or 12mm.

Heated Screeds

Suitable for use over sand/cement screeds with water fed underfloor heating encased within. Adhesive fixing method will be required.

NOTE: For further information on other backgrounds and preparation, contact BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE.

Cutting the BAL BOARD (BAL BOARD 6mm and 12mm)

Easy to cut, score and snap. BAL BOARD only requires a suitable utility knife just score the board and snap. No special tools needed.

1. Mark out the area to be cut and using a straight edge as a guide, score down the board using a utility knife, making sure to slice through the glass fibre mesh.
2. Pull the board edge towards you and snap the board.
3. Cut out for areas of fittings and fixtures should be done before installing the board.

Painted and Wallpaper Finishes

Preparation procedure when painting or wallpapering Internal dry areas

1. The BAL BOARD must be installed with the smooth face outwards.
2. Wipe the face of the board with a damp cloth and leave to dry.
3. All screw fixings and board joints must be filled used the appropriate decorating filler before painting or wallpapering.

HEALTH & SAFETY INFORMATION / GOOD PRACTICE ADVICE

When cutting, always use a dust mask and suitable eye protection. It is always advisable to wear protective gloves when undertaking cutting of any material.

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

POWERSPEC

A unique computerised online specification system for the design and installation of ceramic, mosaic and natural stone tiling. Visit: www.powerspeconline.com

SHELF LIFE

Not applicable if stored correctly under normal dry conditions. Protect from frost and damp.

QUALITY AND ENVIRONMENTAL STANDARDS

Certified by the BBA (British Board of Agreement).

25 YEAR GUARANTEE

All BAL products are supplied with a 25 year product guarantee to be free from manufacturing defects and to be fit for purpose. The guarantee covers materials replacement costs and labour.

This guarantee is subject to use of product in accordance with BAL's instructions and technical data, and good working practice. No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control. *Contact BAL Marketing Department for full details.*

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale. *Available on request.*

For sales and technical queries, contact:

BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, England
www.bal-adhesives.com

Sales

Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical

Tel: +44 (0) 1782 591120 or

+44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

Ireland

Unit 622, Phase III, Northwest Business Park

Ballycoolin, Dublin 15, Ireland

Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.

PorcelBond Plus™ is a trademark of Building Adhesives Ltd