

**DECLARATION OF PERFORMANCE**  
**In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No. 574/2014**  
**for the product BAL Level Out**  
**No. BAL 072-CPR/2013**

1. Unique identification code of the product-type:

**EN 13813:2002**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Cementitious screed material for use internally and externally.**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**Building Adhesives Limited,  
Newstead Industrial Estate,  
Longton Road,  
Trentham,  
Stoke on Trent,  
Staffordshire,  
ST4 8JB**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 4**

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 13813:2002**

**Building Adhesives Limited performed the determination of the product type on the basis of type testing of the product and factory production control testing under attestation system 4.**  
**Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards cementitious screeds, calcium sulphate screeds and synthetic floor resin screeds.**

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:


**Not applicable**

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 13813:2002
Release of corrosive substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Mechanical resistance Compressive strength Flexural strength Wear resistance	$\geq 30 \text{ Nmm}^{-2}$ $\geq 7 \text{ Nmm}^{-2}$ NPD	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 amended by Commission Delegated Regulation (EU) No. 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – UK Head of R+D



Stoke on Trent 08.09.21