



**DECLARATION OF PERFORMANCE**  
**In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.**  
**for the product BAL Absolute Grout White.**

**No BAL-074**

1. Unique identification code of the product-type:  
**EN 12004:2007 + A1:2012**
  
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Improved reaction resin adhesive.**
  
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):  
**Building Adhesives Limited,  
Newstead Industrial Estate,  
Longton Road,  
Trentham,  
Stoke on Trent,  
Staffordshire,  
ST4 8JB**
  
4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
**Not applicable**
  
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3**
  
- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**EN 12004:2007+A1:2012**

**The Notified Body 0370 carried out the determination of the product type on the basis of type testing on samples provided on behalf of Building Adhesives Limited under System 3 and issued test report 21/32301129. Reaction to fire performance has been declared in accordance with the Commission Decision of 9<sup>th</sup> February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.**

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**Not applicable**
  
7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	$\geq 2.0\text{Nmm}^{-2}$	
Durability for; - shear adhesion strength after water immersion - shear adhesion strength after thermal shock	$\geq 2.0\text{Nmm}^{-2}$ $\geq 2.0\text{Nmm}^{-2}$	
Release of dangerous substances	See MSDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D



Stoke on Trent 24/11/22



Building Adhesives Limited, Longton Road, Trentham, Stoke on Trent, ST4 8JB www.building-adhesives.com 22	
BAL 074 EN 12004:2007 +A1:2012 BAL Absolute Grout White Improved reaction resin adhesive	
Reaction to fire	Class E
Release of dangerous substances	See MSDS
Bond strength, as: Initial shear adhesion strength	$\geq 2.0\text{Nmm}^{-2}$
Durability, for: Shear adhesion strength after water immersion	$\geq 2.0\text{Nmm}^{-2}$
Shear adhesion strength after thermal shock	$\geq 2.0\text{Nmm}^{-2}$