



DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.

No. BAL-022

1. Unique identification code of the product-type:
BAL Supercover Rapidset Flexible Grey
2. Intended use:
Fast setting deformable cementitious adhesive with reduced slip for internal and external tiling
3. Manufacturer:
**Building Adhesives Limited,
Newstead Industrial Estate,
Longton Road,
Trentham,
Stoke on Trent,
Staffordshire,
ST4 8JB**
4. Authorised representative:
Not applicable
5. System or systems of AVCP:
System 3
- 6a. Harmonised standard:
EN 12004:2007+A1:2012

The Notified Body 0432 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report 220007054-08-02.

- 6b. European Assessment Document:
Not applicable
7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	NPD	EN 12004:2007 +A1:2012
Bond strength as: - early tensile adhesion strength - initial tensile adhesion strength	$\geq 0.5\text{Nmm}^{-2}$ $\geq 0.5\text{Nmm}^{-2}$	
Durability for; - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion after freeze thaw cycles	$\geq 0.5\text{Nmm}^{-2}$ $\geq 0.5\text{Nmm}^{-2}$ $\geq 0.5\text{Nmm}^{-2}$	
Release of dangerous substances	See SDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D

Stoke on Trent 17/11/22

**UK
CA**

0432

Building Adhesives Limited
www.building-adhesives.com
22

BAL 022
EN 12004:2007 +A1:2012
BAL Supercover Rapidset Flexible Grey
Fast setting deformable cementitious adhesive with reduced slip
for internal and external tiling

Reaction to fire	NPD
Release of dangerous substances	See MSDS
Bond strength, as:	
Early tensile adhesion strength	$\geq 0.5\text{Nmm}^{-2}$
Initial tensile adhesion strength	$\geq 0.5\text{Nmm}^{-2}$
Durability, for:	
Tensile adhesion strength after heat ageing	$\geq 0.5\text{Nmm}^{-2}$
Tensile adhesion strength after water immersion	$\geq 0.5\text{Nmm}^{-2}$
Tensile adhesion strength after freeze/thaw cycles	$\geq 0.5\text{Nmm}^{-2}$