



BAL RAPID FLEX FIBRE PLUS

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name BAL RAPID FLEX FIBRE PLUS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Cement based adhesive.

Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier

Company Identification Building Adhesives Limited

Address Longton Road

Trentham

Stoke on Trent

Postal code ST4 8JB

Telephone: +44 (0)1782 591100

Fax Not known.

E-mail sdsreply@building-adhesives.com

Office hours 8:30am-5pm, Mon-Fri (excluding bank holidays)

1.4 Emergency telephone number

Emergency Phone No. 01865 407 333 (24/7 all year)

Contact No information available.

National response centre

Address NHS Direct

Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GB CLP Regulation, UK SI Skin Irrit. 2 :Causes skin irritation.

2019/720 and UK SI 2020/1567 Skin Sens. 1B :May cause an allergic skin reaction.

Eye Dam. 1 :Causes serious eye damage.

STOT SE 3 :May cause respiratory irritation.

2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567

Product Name BAL RAPID FLEX FIBRE PLUS

Hazard Pictogram(s)



GHS05



GHS07

Signal Word(s)

Danger

Hazard Statement(s)

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.



BAL RAPID FLEX FIBRE PLUS

H335: May cause respiratory irritation.

Precautionary Statement(s) P102: Keep out of reach of children.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501: Dispose of contents in accordance with local, state or national legislation.

2.3 Other hazards

When the cement-based powder is mixed with water or admixture, a strongly alkaline paste is produced. Cement-based products may, until set, cause both irritant and allergic contact dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts. Corrosive. Prolonged contact causes serious eye and tissue damage.

2.4 Additional Information

Contains Ordinary Portland Cement, Calcium Sulphoaluminate Cement. The product contains a reducing agent to ensure that the CrVI content of the cement in the product remains below 2ppm during the defined shelf life of the product.
 The product is not expected to be hazardous to the environment.
 For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Quartz (SiO ₂)	14808-60-7	238-878-4	50-70	Not classified	None
Ordinary Portland Cement	65997-15-1	266-043-4	20-30	Skin Irrit. 2 H315 Skin Sens. 1B H317 Eye Dam. 1 H318 STOT SE 3 H335	GHS05 GHS07
Calcium Sulphoaluminate Cement	65997-15-1	266-043-4	<10	Skin Irrit. 2 H315 Skin Sens. 1B H317 Eye Dam. 1 H318	GHS05 GHS07



BAL RAPID FLEX FIBRE PLUS

				STOT SE 3 H335	
Limestone	1317-65-3	215-279-6	<10	Not classified	None
Lithium carbonate	554-13-2	209-062-5	<1	Acute Tox. 4 H302 Eye Irrit. 2 H319	GHS07
Sodium carbonate	497-19-8	207-838-8	<1	Eye Irrit. 2 H319	GHS07
Tin sulphate	7488-55-3	231-302-2	<1	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Dam. 1 H318 STOT RE 2 H373	GHS05 GHS08 GHS07

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see Medical Advice on this label).
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor.
Ingestion	Treat symptomatically.

4.2 Most important symptoms and effects, both acute and delayed

Causes burns. Allergic contact dermatitis.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment (see Medical Advice on this label). Immediately call a POISON CENTRE/doctor. Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media	As appropriate for surrounding fire.
Unsuitable extinguishing media	None.

5.2 Special hazards arising from the substance or mixture

May decompose in a fire, giving off toxic and irritant vapours.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid dust generation. Do not breathe dust. Ensure full personal protection (including respiratory protection) during removal of spillages.



BAL RAPID FLEX FIBRE PLUS

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Sweep up spilled substance and remove to safe place. Use vacuum equipment for collecting spilt materials, where practicable. Avoid contact with skin or inhalation of spillage or dust. Dampen spillage with water. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers and remove from the area as soon as possible. Flush contaminated area with plenty of water.

6.4 Reference to other sections

See also section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid breathing dust. Wash hands and exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep out of reach of children.

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

None known.

7.3 Specific end use(s)

See 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure

Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Silica, respirable crystalline (respirable fraction)	14808-60-7		0.1			(t)
Portland cement inhalable dust	65997-15-1		10			
Portland cement respirable dust	65997-15-1		4			
Calcium carbonate inhalable dust	1317-65-3		10			
Calcium carbonate respirable dust	1317-65-3		4			



BAL RAPID FLEX FIBRE PLUS

Limestone total inhalable	1317-65-3		10			
Limestone respirable	1317-65-3		4			
Marble total inhalable	1317-65-3		10			
Marble respirable	1317-65-3		4			
Tin compounds, inorganic except SnH ₄ , (as Sn)	7488-55-3		2		4	

Region Source
 United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
 (t) Carc (where generated as a result of a work process)

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection Normally no personal respiratory protection is necessary. If ventilation is inadequate, suitable respiratory protection must be worn. Use respiratory equipment with particle filter P2.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Solid.
 Colour : Off-white
 Odour Almost colourless
 Odour threshold Not known.
 pH >11.5
 Melting point/freezing point Not known.
 Initial boiling point and boiling range Not known.
 Flash Point Not applicable.
 Evaporation rate Not known.
 Flammability (solid, gas) Not known.



BAL RAPID FLEX FIBRE PLUS

Upper/lower flammability or explosive limits	Not known.
Vapour pressure	Not known.
Vapour density	Not known.
Density (g/ml)	Not known.
Relative density	Not known.
Solubility(ies)	Solubility (Water) : Very slightly soluble Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	Not known.
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Not known.
Oxidising properties	Not known.
9.2 Other information	None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

None anticipated.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

Fire creates: carbon monoxide, carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 833333.31
Acute toxicity - Skin Contact	Calculation method : Not classified.
Acute toxicity - Inhalation	Calculation method : Not classified.
Skin corrosion/irritation	Calculation method : Causes skin irritation.
Serious eye damage/irritation	Calculation method : Causes serious eye damage.
Skin sensitization data	Calculation method : May cause an allergic skin reaction.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified.
Carcinogenicity	Calculation method : Not classified.
Reproductive toxicity	Calculation method : Not classified.
Lactation	Calculation method : Not classified.



BAL RAPID FLEX FIBRE PLUS

STOT - single exposure	Calculation method : May cause respiratory irritation. Cement dust may irritate the throat and respiratory tract. Based on available data, the classification criteria are not met.
STOT - repeated exposure	Calculation method : not classified. There is an indication of Chronic Obstructive Pulmonary Disease (COPD). The effects are acute and due to high exposures. No chronic effects or effects at low concentration have been observed.
Aspiration hazard	Calculation method : Not classified.
11.2 Other information	Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish.
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment	Not classified.
Compartment	
Toxicity - Terrestrial	Not classified.
Compartment	

12.2 Persistence and degradability

After hydration, cement presents no toxicity risk.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Partly miscible in water.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator. Dispose at suitable refuse site.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

Not classified as hazardous for transport.

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable



BAL RAPID FLEX FIBRE PLUS

- 14.3 Transport hazard class(es)** Not applicable
- 14.4 Packing group** Not applicable
- 14.5 Environmental hazards** Not classified as a Marine Pollutant.
- 14.6 Special precautions for user** Not known
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not known

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances of Very High Concern for Authorisation Not listed

UK REACH Authorisation List (Annex XIV) list of substances subject to authorisation Not listed

UK REACH Restrictions List (Annex XVII) Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Cement, portland, chemicals (65997-15-1), Calcium Sulphoaluminate Cement (), lithium carbonate (554-13-2), citric acid (77-92-9), sodium carbonate (497-19-8), Tin sulphate (7488-55-3)

UK REACH Rolling Action Plan (RAP) Not listed

The Persistent Organic Pollutants Regulations 2007 (SI 2007/3106) as amended Not listed

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583) Not listed

The Prior Informed Consent (PIC) Regulations concerning the export and import of hazardous chemicals SI2008/2108 as amended Not listed

European Regulations - Authorisations and/or Restrictions On Use Community Rolling Action Plan (CoRAP) Tin sulphate (7488-55-3)

European Regulations - Authorisations and/or Restrictions On Use Community Rolling Action Plan (CoRAP) Tin sulphate (7488-55-3)

15.2 Chemical Safety Assessment

United Kingdom A REACH chemical safety assessment has not been carried out.

United Kingdom A REACH chemical safety assessment has not been carried out.

United Kingdom A REACH chemical safety assessment has not been carried out.

United Kingdom A REACH chemical safety assessment has not been carried out.



BAL RAPID FLEX FIBRE PLUS

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS05



GHS07

GHS08: GHS: Health hazard

Hazard classification

Acute Tox. 4 : Acute toxicity, Category 4
 Skin Irrit. 2 : Skin corrosion/irritation, Category 2
 Skin Sens. 1 : Skin sensitization, Category 1
 Skin Sens. 1B : Skin sensitization, Category 1B
 Eye Dam. 1 : Serious eye damage/irritation, Category 1
 Eye Irrit. 2 : Serious eye damage/irritation, Category 2
 STOT SE 3 : Specific target organ toxicity — single exposure, Category 3
 STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

Hazard Statement(s)

H302: Harmful if swallowed.
 H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H318: Causes serious eye damage.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

P102: Keep out of reach of children.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264: Wash hands and exposed skin thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310: Immediately call a POISON CENTRE/doctor.
 P312: Call a POISON CENTRE/doctor if you feel unwell.



BAL RAPID FLEX FIBRE PLUS

P321: Specific treatment (see Medical Advice on this label).
 P332+P313: If skin irritation occurs: Get medical advice/attention.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364: Take off contaminated clothing and wash it before reuse.
 P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P405: Store locked up.
 P501: Dispose of contents in accordance with local, state or national legislation.

ATE : Acute Toxicity Estimate
 CAS : Chemical Abstracts Service
 DNEL : Derived No Effect Level
 EC : European Community
 EINECS : European Inventory of Existing Commercial Chemical Substances
 LTEL : Long term exposure limit
 PBT : Persistent, Bioaccumulative and Toxic
 PNEC : Predicted No Effect Concentration
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 STEL : Short term exposure limit
 STOT : Specific Target Organ Toxicity
 vPvB : very Persistent and very Bioaccumulative

Acronyms

Issued by:

Head of R+D

Issue number:

01

Key literature references and sources for data used to compile the SDS

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. BUILDING ADHESIVES LIMITED gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. BUILDING ADHESIVES LIMITED accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.