

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier				
Product Name	BAL SINGLE PART FASTFLEX WHITE			
1.2 Relevant identified uses of	the substance or mixture and uses advised against			
Identified Use(s)	Cement based adhesive.			
Uses Advised Against	Not known.			
1.3 Details of the supplier of th	e safety data sheet			
Manufacturer/Supplier				
Company Identification	Building Adhesives Limited			
Address	Longton Road			
	Trentham			
	Stoke on Trent			
Postal code	ST4 8JB			
Telephone:	+44 (0)1782 591100			
Fax	Not known.			
E-mail	sdsreply@building-adhesives.com			
Office hours	8:30am-5pm, Mon-Fri (excluding bank holidays)			
1.4 Emergency telephone numl				
Emergency Phone No.	01865 407 333 (24/7 all year)			
Contact	No information available.			
National response centre				
Address	NHS Direct			
Emergency Phone No.	+44 111			
SECTION 2: HAZARDS IDENTIFIC	ATION			
2.1 Classification of the substar	nce or mixture			
	Skin Irrit. 2 :Causes skin irritation.			
2.1 Classification of the substar GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	Skin Irrit. 2 :Causes skin irritation.			
GB CLP Regulation, UK SI	Skin Irrit. 2 :Causes skin irritation.			
GB CLP Regulation, UK SI	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction.			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage.			
GB CLP Regulation, UK SI	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation.			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE 			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE 			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name	 Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE 			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s) Signal Word(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE $\overbrace{GHS05}^{CF}GHS05}^{CF}GHS05}$			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE GHS05 Danger H315: Causes skin irritation.			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s) Signal Word(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s) Signal Word(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s) Signal Word(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			
GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 2.2 Label elements Product Name Hazard Pictogram(s) Signal Word(s)	Skin Irrit. 2 :Causes skin irritation. Skin Sens. 1B :May cause an allergic skin reaction. Eye Dam. 1 :Causes serious eye damage. STOT SE 3 :May cause respiratory irritation. According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 BAL SINGLE PART FASTFLEX WHITE			



Precautionary Statement(s)	 P102: Keep out of reach of children. P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501: Dispose of contents in accordance with local, state or national legislation.
2.3 Other hazards	When the cement-based powder is mixed with water or admixture, a strongly alkaline paste is produced. Cement-based products may, until set, cause both irritant and allergic contact dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts. Corrosive. Prolonged contact causes serious eye and tissue damage.
2.4 Additional Information	Contains Ordinary Portland Cement. The product is not expected to be hazardous to the environment. For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS	CAS No.	EC No. /	%W/W	Hazard Statement(s)	Hazard
INGREDIENT(S)		Registration			Pictogram(s)
		number(s)			
Ordinary Portland	65997-15-1	266-043-4	30-40	Skin Irrit. 2 H315	GHS05
Cement				Skin Sens. 1B H317	GHS07
				Eye Dam. 1 H318	
				STOT SE 3 H335	
Quartz (SiO2)	14808-60-7	238-878-4	20-30	Not classified	None
Calcium aluminate	65997-16-2	266-045-5	<10	Not classified	None
cement					
Limestone	1317-65-3	215-279-6	<10	Not classified	None
Hydrated Lime	1305-62-0	215-137-3	<2	Skin Irrit. 2 H315	GHS05
				Eye Dam. 1 H318	GHS07
				STOT SE 3 H335	





	554-13-2	209-062-5	<1	Acute Tox. 4 H302 Eye Irrit. 2 H319	GHS07
Citric acid	77-92-9	201-069-1	<1	Eye Irrit. 2 H319	GHS07
Tartaric acid	87-69-4	201-766-0	<1	Eye Dam. 1 H318	GHS05

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid meas	sures
Inhalation	Remove person to fresh air and keep comfortable for breathing.
	Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Take off immediately all contaminated clothing and wash it before
	reuse. If skin irritation occurs: Get medical advice/attention.
	Specific treatment (see Medical Advice on this label).
Eye Contact	Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing. Immediately
	call a POISON CENTRE/doctor.
Ingestion	Treat symptomatically.
4.2 Most important symptoms	and effects, both acute and delayed
	Causes burns. Allergic contact dermatitis.
4.3 Indication of any immediate	e medical attention and special treatment needed
	Specific treatment (see Medical Advice on this label). Immediately
	call a POISON CENTRE/doctor. Treat symptomatically.
SECTION 5: FIREFIGHTING MEAS	URES
5.1 Extinguishing media	
Suitable Extinguishing media	As appropriate for surrounding fire.
Unsuitable extinguishing media	None.
5.2 Special hazards arising from	the substance or mixture
	May decompose in a fire, giving off toxic and irritant vapours.
5.3 Advice for firefighters	
	Fire fighters should wear complete protective clothing including
	self-contained breathing apparatus.
SECTION 6: ACCIDENTAL RELEAS	E MEASURES
6.1 Personal precautions, prote	ctive equipment and emergency procedures Provide adequate ventilation. Avoid dust generation. Do not
	breathe dust. Ensure full personal protection (including respiratory
	protection) during removal of spillages.
6.2 Environmental precautions	protection during removal of spinages.
0.2 Environmental precautions	Spillages or uncontrolled discharges into watercourses must be
	alerted to the appropriate regulatory body.
6.3 Methods and material for c	ontainment and cleaning up
	Sweep up spilled substance and remove to safe place. Use vacuum
	equipment for collecting spilt materials, where practicable. Avoid
	contact with skin or inhalation of spillage or dust. Dampen spillage

with water. Absorb in vermiculite, dry sand or earth and place into





containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers and remove from the area as soon as possible. Flush contaminated area with plenty of water.


6.4 Reference to other section	IS
	See also section 8, 13.
SECTION 7: HANDLING AND STO	ORAGE
7.1 Precautions for safe handl	ing
	Avoid breathing dust. Wash hands and exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
7.2 Conditions for safe storage	e, including any incompatibilities
	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep out of reach of children.
Storage temperature	Ambient.
Storage life	Stable under normal conditions.
Incompatible materials 7.3 Specific end use(s)	None known.
	See 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Silica, respirable crystalline (respirable fraction)	14808-60-7		0.1			(t)
Portland cement inhalable dust	65997-15-1		10			
Portland cement respirable dust	65997-15-1		4			
Hydrated lime	1305-62-0		5			
Hydrated lime - Respirable fraction	1305-62-0		1		4	
Calcium carbonate inhalable dust	1317-65-3		10			
Calcium carbonate respirable dust	1317-65-3		4			
Limestone total inhalable	1317-65-3		10			
Limestone respirable	1317-65-3		4			
Marble total inhalable	1317-65-3		10			
Marble respirable	1317-65-3		4			





Calcium aluminate cement inhalable dust	65997-16-2	10		
Calcium aluminate cement	65997-16-2	4		
respirable dust				

Region Source

United	UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)
Kingdom	

Remark Notes

(t) Carc (where generated as a result of a work process)

8.2 Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.
8.2.2. Personal protection	
equipment	
Eye Protection	Wear eye protection with side protection (EN166).
Skin protection	Wear protective clothing and gloves: Impervious gloves (EN 374).
Respiratory protection	Normally no personal respiratory protection is necessary. If ventilation is inadequate, suitable respiratory protection must be worn. Use respiratory equipment with particle filter P2.
Thermal hazards	None known.

8.2.3. Environmental Exposure Avoid release to the environment. Controls

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · ·
Appearance	Solid.
	Colour : Off-white
Odour	Almost colourless
Odour threshold	Not known.
рН	>11.5
Melting point/freezing point	Not known.
Initial boiling point and boiling	Not known.
range	
Flash Point	Not applicable.
Evaporation rate	Not known.
Flammability (solid, gas)	Not known.
Upper/lower flammability or	Not known.
explosive limits	
Generated by HazMix™	Page: 5 - 10





Vapour pressure	Not known.
Vapour density	Not known.
Density (g/ml)	Not known.
Relative density	Not known.
Solubility(ies)	Solubility (Water) : Very slightly soluble
	Solubility (Other) : Not known.
Partition coefficient: n-	Not known.
octanol/water	
Auto-ignition temperature	Not known.
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Not known.
Oxidising properties	Not known.
9.2 Other information	

None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

	None anticipated.	
10.2 Chemical Stability		
	Stable under normal conditions.	
10.3 Possibility of hazardous reactions		
	No hazardous reactions known if used for its intended purpose.	
10.4 Conditions to avoid		
	None anticipated.	
10.5 Incompatible materials		
	Not known.	
10.6 Hazardous decomposition products		
	Fire creates: carbon monoxide, carbon dioxide.	

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 833333.31
Acute toxicity - Skin Contact	Calculation method : Not classified.
Acute toxicity - Inhalation	Calculation method : Not classified.
Skin corrosion/irritation	Calculation method : Causes skin irritation.
Serious eye damage/irritation	Calculation method : Causes serious eye damage.
Skin sensitization data	Calculation method : May cause an allergic skin reaction.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified.
Carcinogenicity	Calculation method : Not classified.
Reproductive toxicity	Calculation method : Not classified.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : May cause respiratory irritation. Cement dust may irritate the throat and respiratory tract. Based on available data, the classification criteria are not met.





STOT - repeated exposure	Calculation method : not classified. There is an indication of
	Chronic Obstructive Pulmonary Disease (COPD). The effects are
	acute and due to high exposures. No chronic effects or effects at
	low concentration have been observed.
Aspiration hazard	Calculation method : Not classified.
11.2 Other information	

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.	
Toxicity - Fish	Low toxicity to fish.	
Toxicity - Algae	Low toxicity to algae.	
Toxicity - Sediment	Not classified.	
Compartment		
Toxicity - Terrestrial	Not classified.	
Compartment		
12.2 Persistence and degradability		
	After hydration, cement presents no toxicity risk.	
12.3 Bioaccumulative potential		
	Not known.	
12.4 Mobility in soil		
	Partly miscible in water.	
12.5 Results of PBT and vPvB as	sessment	
	Not classified as PBT or vPvB.	
12.6 Other adverse effects		
	Not known.	
SECTION 13: DISPOSAL CONSIDE	RATIONS	
13.1 Waste treatment methods		
	Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator.	
	Dispose at suitable refuse site.	
13.2 Additional Information		
	Disposal should be in accordance with local, state or national	
	legislation.	
SECTION 14: TRANSPORT INFOR	MATION	

Not classified as hazardous for transport.

- 14.1 UN number
- **14.2 UN proper shipping name**
- Not applicable
- 14.3 Transport hazard class(es) Not applicable
- 14.4 Packing group

Not applicable





14.5 Environmental hazards

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not known

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture United Kingdom Regulations - Authorisations and/or Restrictions On Use UK REACH Candidate List of Not listed Substances of Very High Concern for Authorisation **UK REACH Authorisation List** Not listed (Annex XIV) list of substances subject to authorisation **UK REACH Restrictions List** Cement, portland, chemicals (65997-15-1), lithium carbonate (Annex XVII) Restrictions on the (554-13-2), citric acid (77-92-9), manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **UK REACH Rolling Action Plan** Not listed (RAP) The Persistent Organic Pollutants Not listed Regulations 2007 (SI 2007/3106) as amended The Ozone-Depleting Substances Not listed and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583) The Prior Informed Consent (PIC) Not listed Regulations concerning the export and import of hazardous chemicals SI2008/2108 as amended European Regulations - Authorisations and/or Restrictions On Use **Community Rolling Action Plan** (CoRAP) 15.2 Chemical Safety Assessment United Kingdom A REACH chemical safety assessment has not been carried out.





SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)	A CONTRACTOR	
	GHS05	GHS07
	GHS08: GHS: Health hazard	
Hazard classification	Acute Tox. 4 : Acute toxicity, Ca Skin Irrit. 2 : Skin corrosion/irri Skin Sens. 1 : Skin sensitization Skin Sens. 1B : Skin sensitizatio Eye Dam. 1 : Serious eye dama Eye Irrit. 2 : Serious eye damag STOT SE 3 : Specific target orga Category 3 STOT RE 2 : Specific target orga Category 2	tation, Category 2 , Category 1 n, Category 1B ge/irritation, Category 1 e/irritation, Category 2
Hazard Statement(s)	H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic sk H318: Causes serious eye dama H319: Causes serious eye irrita H335: May cause respiratory ir H373: May cause damage to or exposure.	age. tion.
Precautionary Statement(s)	 P271: Use only outdoors or in a P272: Contaminated work cloth the workplace. P280: Wear protective gloves/ protection/face protection. P302+P352: IF ON SKIN: Wash P304+P340: IF INHALED: Remote comfortable for breathing. P305+P351+P338: IF IN EYES: F 	me/gas/mist/vapours/spray. d skin thoroughly after handling. a well-ventilated area. hing should not be allowed out of protective clothing/eye with plenty of water. ove person to fresh air and keep Rinse cautiously with water for act lenses, if present and easy to do.
Generated by HazMix™	Page: 9 - 10	Revision: 1





Acronyms	 P321: Specific treatment (see Medical Advice on this label). P332+P313: If skin irritation occurs: Get medical advice/attention. P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up. P501: Dispose of contents in accordance with local, state or national legislation. ATE : Acute Toxicity Estimate CAS : Chemical Abstracts Service DNEL : Derived No Effect Level EC : European Community EINECS : European Inventory of Existing Commercial Chemical Substances LTEL : Long term exposure limit PBT : Presistent, Bioaccumulative and Toxic PNEC : Predicted No Effect Concentration REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals STDT : Specific Target Organ Toxicity vPvB : very Persistent and very Bioaccumulative
Issued by:	Head of R+D
Issue number:	01
Key literature references and	GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567
sources for data used to compil	e
the SDS Disclaimers	Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. BUILDING ADHESIVES LIMITED gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. BUILDING ADHESIVES LIMITED accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.