DECLARATION OF PERFORMANCE
In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.

No. BAL-002

1. Unique identification code of the product-type:

BAL Bluestar

2. Intended use:

Normal dispersion adhesive with reduced slip and extended open time for internal wall tiling.

3. Manufacturer:

Building Adhesives Limited,
Newstead Industrial Estate,
Longton Road,
Trentham,
Stoke on Trent,
Staffordshire,
ST4 8JB

4. Authorised representative:

Not applicable

5. System or systems of AVCP:

System 3

6a. Harmonised standard:

EN 12004:2007+A1:2012

The Notified Body 0370 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report 13/6382-257.
Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.

6b. European Assessment Document:

Not applicable

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	**Class E**	**EN 12004:2007 +A1:2012**
Bond strength as: **- initial shear adhesion strength**	**≥ 1.0Nmm^{-2}**	
Durability for; **- shear adhesion strength after heat ageing**	**≥ 1.0Nmm^{-2}**	
Release of dangerous substances	**See SDS**	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D

David Longwell

Stoke on Trent 16/11/22

UK CA

0370

Building Adhesives Limited
www.building-adhesives.com
22

BAL 002
EN 12004:2007 +A1:2012
BAL BLUESTAR
Normal dispersion adhesive with reduced slip
and extended open time for internal wall tiling

Reaction to fire	Class E
Release of dangerous substances	See SDS
Bond strength, as: Initial shear adhesion strength Durability, for: Shear adhesion strength after heat ageing	 ≥ 1.0Nmm^{-2} ≥ 1.0Nmm^{-2}