DECLARATION OF PERFORMANCE
In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.

No. BAL-053

1. Unique identification code of the product-type:

BAL Turboset White

2. Intended use:

Improved fast setting cementitious adhesive for internal and external tiling

3. Manufacturer:

Building Adhesives Limited,
Newstead Industrial Estate,
Longton Road,
Trentham,
Stoke on Trent,
Staffordshire,
ST4 8JB

4. Authorised representative:

Not applicable

5. System or systems of AVCP:

System 3

6a. Harmonised standard:

EN 12004:2007+A1:2012

The Notified Body 0370 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report 14/9311-1943.
Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.

6b. European Assessment Document:

Not applicable

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	**Class E**	**EN 12004:2007 +A1:2012**
Bond strength as: - **early tensile adhesion strength** - **initial tensile adhesion strength**	**≥ 0.5Nmm^{-2}** **≥ 1.0Nmm^{-2}**	
Durability for; - **tensile adhesion strength after heat ageing** - **tensile adhesion strength after water immersion** - **tensile adhesion after freeze thaw cycles**	**≥ 1.0Nmm^{-2}** **≥ 1.0Nmm^{-2}** **≥ 1.0Nmm^{-2}**	
Release of dangerous substances	**See SDS**	

8. The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D

Stoke on Trent 18/11/22

UK
CA
0370

Building Adhesives Limited
www.building-adhesives.com
22

BAL 053
EN 12004:2007 +A1:2012
BAL Turboset White
Improved fast setting cementitious adhesive for
internal and external tiling

Reaction to fire	Class E
Release of dangerous substances	See MSDS
Bond strength, as:	
Early tensile adhesion strength	≥ 0.5Nmm^{-2}
Initial tensile adhesion strength	≥ 1.0Nmm^{-2}
Durability, for:	
Tensile adhesion strength after heat ageing	≥ 1.0Nmm^{-2}
Tensile adhesion strength after water immersion	≥ 1.0Nmm^{-2}
Tensile adhesion strength after freeze/thaw cycles	≥ 1.0Nmm^{-2}