



## BAL SINGLE PART FASTFLEX GREY

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product Name BAL SINGLE PART FASTFLEX GREY

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Cement based adhesive.

Uses Advised Against Not known.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier

Company Identification Building Adhesives Limited

Address Longton Road

Trentham

Stoke on Trent

Postal code

ST4 8JB

Telephone:

+44 (0)1782 591100

Fax

Not known.

E-mail

sdsreply@building-adhesives.com

Office hours

8:30am-5pm, Mon-Fri (excluding bank holidays)

#### 1.4 Emergency telephone number

Emergency Phone No. 01865 407 333 (24/7 all year)

Contact No information available.

National response centre

Address

NHS Direct

Emergency Phone No.

+44 111

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

GB CLP Regulation, UK SI Skin Irrit. 2 :Causes skin irritation.

2019/720 and UK SI 2020/1567 Skin Sens. 1B :May cause an allergic skin reaction.

Eye Dam. 1 :Causes serious eye damage.

STOT SE 3 :May cause respiratory irritation.

#### 2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567

Product Name

BAL SINGLE PART FASTFLEX GREY

Hazard Pictogram(s)



GHS05



GHS07

Signal Word(s)

Danger

Hazard Statement(s)

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.



## BAL SINGLE PART FASTFLEX GREY

Precautionary Statement(s) P102: Keep out of reach of children.  
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P501: Dispose of contents in accordance with local, state or national legislation.

### 2.3 Other hazards

When the cement-based powder is mixed with water or admixture, a strongly alkaline paste is produced. Cement-based products may, until set, cause both irritant and allergic contact dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts. Corrosive. Prolonged contact causes serious eye and tissue damage.

### 2.4 Additional Information

Contains Ordinary Portland Cement, Calcium Sulphoaluminate Cement. The product contains a reducing agent to ensure that the CrVI content of the cement in the product remains below 2ppm during the defined shelf life of the product.  
 The product is not expected to be hazardous to the environment.  
 For full text of H/P Statements see section 16.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Not applicable.

### 3.2 Mixtures

| HAZARDOUS INGREDIENT(S)        | CAS No.    | EC No. / Registration number(s) | %W/W  | Hazard Statement(s)                                                           | Hazard Pictogram(s) |
|--------------------------------|------------|---------------------------------|-------|-------------------------------------------------------------------------------|---------------------|
| Ordinary Portland Cement       | 65997-15-1 | 266-043-4                       | 20-30 | Skin Irrit. 2 H315<br>Skin Sens. 1B H317<br>Eye Dam. 1 H318<br>STOT SE 3 H335 | GHS05<br>GHS07      |
| Calcium Sulphoaluminate Cement | 65997-15-1 | 266-043-4                       | <10   | Skin Irrit. 2 H315<br>Skin Sens. 1B H317<br>Eye Dam. 1 H318<br>STOT SE 3 H335 | GHS05<br>GHS07      |
| Rubber crumb                   |            |                                 | 20-40 | Not classified                                                                | None                |
| Limestone                      | 1317-65-3  | 215-279-6                       | <15   | Not classified                                                                | None                |



## BAL SINGLE PART FASTFLEX GREY

|                   |           |           |    |                                                                              |                         |
|-------------------|-----------|-----------|----|------------------------------------------------------------------------------|-------------------------|
| Lithium carbonate | 554-13-2  | 209-062-5 | <1 | Acute Tox. 4 H302<br>Eye Irrit. 2 H319                                       | GHS07                   |
| Tin sulphate      | 7488-55-3 | 231-302-2 | <1 | Skin Irrit. 2 H315<br>Skin Sens. 1 H317<br>Eye Dam. 1 H318<br>STOT RE 2 H373 | GHS05<br>GHS08<br>GHS07 |
| Citric acid       | 77-92-9   | 201-069-1 | <1 | Eye Irrit. 2 H319                                                            | GHS07                   |

For full text of H/P Statements see section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

|              |                                                                                                                                                                                             |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation   | Remove person to fresh air and keep comfortable for breathing.<br>Call a POISON CENTRE/doctor if you feel unwell.                                                                           |
| Skin Contact | Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.<br>Specific treatment (see Medical Advice on this label). |
| Eye Contact  | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor.                               |
| Ingestion    | Treat symptomatically.                                                                                                                                                                      |

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes burns. Allergic contact dermatitis.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment (see Medical Advice on this label). Immediately call a POISON CENTRE/doctor. Treat symptomatically.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

|                                |                                      |
|--------------------------------|--------------------------------------|
| Suitable Extinguishing media   | As appropriate for surrounding fire. |
| Unsuitable extinguishing media | None.                                |

#### 5.2 Special hazards arising from the substance or mixture

May decompose in a fire, giving off toxic and irritant vapours.

#### 5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid dust generation. Do not breathe dust. Ensure full personal protection (including respiratory protection) during removal of spillages.

#### 6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

#### 6.3 Methods and material for containment and cleaning up

Sweep up spilled substance and remove to safe place. Use vacuum equipment for collecting spilt materials, where practicable. Avoid



## BAL SINGLE PART FASTFLEX GREY

contact with skin or inhalation of spillage or dust. Dampen spillage with water. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect and place in suitable waste disposal containers and seal securely. Label the containers and remove from the area as soon as possible. Flush contaminated area with plenty of water.

### 6.4 Reference to other sections

See also section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid breathing dust. Wash hands and exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep out of reach of children.

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

None known.

### 7.3 Specific end use(s)

See 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### 8.1.1 Occupational Exposure

Limits

| Occupational Exposure Limits                               |            |                     |                                    |            |                           |      |
|------------------------------------------------------------|------------|---------------------|------------------------------------|------------|---------------------------|------|
| SUBSTANCE.                                                 | CAS No.    | LTEL (8 hr TWA ppm) | LTEL (8 hr TWA mg/m <sup>3</sup> ) | STEL (ppm) | STEL (mg/m <sup>3</sup> ) | Note |
| Portland cement inhalable dust                             | 65997-15-1 |                     | 10                                 |            |                           |      |
| Portland cement respirable dust                            | 65997-15-1 |                     | 4                                  |            |                           |      |
| Rubber crumb inhalable dust                                |            |                     | 10                                 |            |                           |      |
| Rubber crumb respirable dust                               |            |                     | 5                                  |            |                           |      |
| Calcium carbonate inhalable dust                           | 1317-65-3  |                     | 10                                 |            |                           |      |
| Calcium carbonate respirable dust                          | 1317-65-3  |                     | 4                                  |            |                           |      |
| Limestone total inhalable                                  | 1317-65-3  |                     | 10                                 |            |                           |      |
| Limestone respirable                                       | 1317-65-3  |                     | 4                                  |            |                           |      |
| Marble total inhalable                                     | 1317-65-3  |                     | 10                                 |            |                           |      |
| Marble respirable                                          | 1317-65-3  |                     | 4                                  |            |                           |      |
| Tin compounds, inorganic except SnH <sub>4</sub> , (as Sn) | 7488-55-3  |                     | 2                                  |            | 4                         |      |



## BAL SINGLE PART FASTFLEX GREY

|                |                                                                         |
|----------------|-------------------------------------------------------------------------|
| Region         | Source                                                                  |
| United Kingdom | UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020) |

### 8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection Normally no personal respiratory protection is necessary. If ventilation is inadequate, suitable respiratory protection must be worn. Use respiratory equipment with particle filter P2.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

|                                              |                                            |
|----------------------------------------------|--------------------------------------------|
| Appearance                                   | Solid.                                     |
|                                              | Colour : Dark grey                         |
| Odour                                        | Almost colourless                          |
| Odour threshold                              | Not known.                                 |
| pH                                           | >11.5                                      |
| Melting point/freezing point                 | Not known.                                 |
| Initial boiling point and boiling range      | Not known.                                 |
| Flash Point                                  | Not applicable.                            |
| Evaporation rate                             | Not known.                                 |
| Flammability (solid, gas)                    | Not known.                                 |
| Upper/lower flammability or explosive limits | Not known.                                 |
| Vapour pressure                              | Not known.                                 |
| Vapour density                               | Not known.                                 |
| Density (g/ml)                               | Not known.                                 |
| Relative density                             | Not known.                                 |
| Solubility(ies)                              | Solubility (Water) : Very slightly soluble |
|                                              | Solubility (Other) : Not known.            |



## BAL SINGLE PART FASTFLEX GREY

|                                        |            |
|----------------------------------------|------------|
| Partition coefficient: n-octanol/water | Not known. |
| Auto-ignition temperature              | Not known. |
| Decomposition Temperature (°C)         | Not known. |
| Viscosity                              | Not known. |
| Explosive properties                   | Not known. |
| Oxidising properties                   | Not known. |

### 9.2 Other information

None.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

None anticipated.

### 10.2 Chemical Stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

### 10.4 Conditions to avoid

None anticipated.

### 10.5 Incompatible materials

Not known.

### 10.6 Hazardous decomposition products

Fire creates: carbon monoxide, carbon dioxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

|                                |                                                                                                                                                                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute toxicity - Ingestion     | Calculation method : Not classified.<br>Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 833333.31                                                                                                           |
| Acute toxicity - Skin Contact  | Calculation method : Not classified.                                                                                                                                                                                                 |
| Acute toxicity - Inhalation    | Calculation method : Not classified.                                                                                                                                                                                                 |
| Skin corrosion/irritation      | Calculation method : Causes skin irritation.                                                                                                                                                                                         |
| Serious eye damage/irritation  | Calculation method : Causes serious eye damage.                                                                                                                                                                                      |
| Skin sensitization data        | Calculation method : May cause an allergic skin reaction.                                                                                                                                                                            |
| Respiratory sensitization data | Calculation method : Not classified.                                                                                                                                                                                                 |
| Germ cell mutagenicity         | Calculation method : Not classified.                                                                                                                                                                                                 |
| Carcinogenicity                | Calculation method : Not classified.                                                                                                                                                                                                 |
| Reproductive toxicity          | Calculation method : Not classified.                                                                                                                                                                                                 |
| Lactation                      | Calculation method : Not classified.                                                                                                                                                                                                 |
| STOT - single exposure         | Calculation method : May cause respiratory irritation. Cement dust may irritate the throat and respiratory tract. Based on available data, the classification criteria are not met.                                                  |
| STOT - repeated exposure       | Calculation method : not classified. There is an indication of Chronic Obstructive Pulmonary Disease (COPD). The effects are acute and due to high exposures. No chronic effects or effects at low concentration have been observed. |
| Aspiration hazard              | Calculation method : Not classified.                                                                                                                                                                                                 |
| <b>11.2 Other information</b>  | Not known.                                                                                                                                                                                                                           |



## BAL SINGLE PART FASTFLEX GREY

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Toxicity - Aquatic invertebrates Low toxicity to invertebrates.

Toxicity - Fish Low toxicity to fish.

Toxicity - Algae Low toxicity to algae.

Toxicity - Sediment Not classified.

Compartment

Toxicity - Terrestrial Not classified.

Compartment

#### 12.2 Persistence and degradability

After hydration, cement presents no toxicity risk.

#### 12.3 Bioaccumulative potential

Not known.

#### 12.4 Mobility in soil

Partly miscible in water.

#### 12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

#### 12.6 Other adverse effects

Not known.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator.  
Dispose at suitable refuse site.

#### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

### SECTION 14: TRANSPORT INFORMATION

**Not classified as hazardous for transport.**

#### 14.1 UN number

Not applicable

#### 14.2 UN proper shipping name

Not applicable

#### 14.3 Transport hazard class(es)

Not applicable

#### 14.4 Packing group

Not applicable

#### 14.5 Environmental hazards

Not classified as a Marine Pollutant.

#### 14.6 Special precautions for user

Not known

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not known



## BAL SINGLE PART FASTFLEX GREY

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of            Not listed

Substances of Very High Concern  
for Authorisation

UK REACH Authorisation List            Not listed

(Annex XIV) list of substances  
subject to authorisation

UK REACH Restrictions List            Cement, portland, chemicals (65997-15-1), Calcium  
(Annex XVII) Restrictions on the    Sulphoaluminate Cement (), lithium carbonate (554-13-2), citric  
manufacture, placing on the       acid (77-92-9), sodium carbonate (497-19-8), Tin sulphate (7488-  
market and use of certain       55-3)

dangerous substances, mixtures  
and articles

UK REACH Rolling Action Plan       Not listed  
(RAP)

The Persistent Organic Pollutants Not listed  
Regulations 2007 (SI 2007/3106)  
as amended

The Ozone-Depleting Substances Not listed  
and Fluorinated Greenhouse  
Gases (Amendment etc.) (EU  
Exit) Regulations 2019 (SI  
2019/583)

The Prior Informed Consent (PIC) Not listed  
Regulations concerning the  
export and import of hazardous  
chemicals SI2008/2108 as  
amended

European Regulations - Authorisations and/or Restrictions On Use

Community Rolling Action Plan    Tin sulphate (7488-55-3)  
(CoRAP)

#### 15.2 Chemical Safety Assessment

United Kingdom                            A REACH chemical safety assessment has not been carried out.

### SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

#### LEGEND

Hazard Pictogram(s)



GHS05



GHS07





## BAL SINGLE PART FASTFLEX GREY

GHS08: GHS: Health hazard

### Hazard classification

Acute Tox. 4 : Acute toxicity, Category 4  
Skin Irrit. 2 : Skin corrosion/irritation, Category 2  
Skin Sens. 1 : Skin sensitization, Category 1  
Skin Sens. 1B : Skin sensitization, Category 1B  
Eye Dam. 1 : Serious eye damage/irritation, Category 1  
Eye Irrit. 2 : Serious eye damage/irritation, Category 2  
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3  
STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

### Hazard Statement(s)

H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H373: May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statement(s)

P102: Keep out of reach of children.  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264: Wash hands and exposed skin thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTRE/doctor.  
P312: Call a POISON CENTRE/doctor if you feel unwell.  
P321: Specific treatment (see Medical Advice on this label).  
P332+P313: If skin irritation occurs: Get medical advice/attention.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
P405: Store locked up.  
P501: Dispose of contents in accordance with local, state or national legislation.



## BAL SINGLE PART FASTFLEX GREY

### Acronyms

ATE : Acute Toxicity Estimate  
CAS : Chemical Abstracts Service  
DNEL : Derived No Effect Level  
EC : European Community  
EINECS : European Inventory of Existing Commercial Chemical Substances  
LTEL : Long term exposure limit  
PBT : Persistent, Bioaccumulative and Toxic  
PNEC : Predicted No Effect Concentration  
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
STEL : Short term exposure limit  
STOT : Specific Target Organ Toxicity  
vPvB : very Persistent and very Bioaccumulative

### Issued by:

Head of R+D

### Issue number:

01

### Key literature references and sources for data used to compile the SDS

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. BUILDING ADHESIVES LIMITED gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. BUILDING ADHESIVES LIMITED accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.